

## FWSG RA

### Ξύστρα για σωλήνες και εξόδους d 25 - d 63

Dimension-bound compact scraper tool for the reliable removal of the oxide layer of HDPE and PE-Xa pipes and at the outlets of FRIALEN safety fittings. Super long scraping length, in the diameter d 32 also for FRIALONG long couplers. Scraper blade made of carbide with 2 edges (twice the service life). Automatic compensation of pipe out-of-roundness and tolerances. Manual operation, with hand crank or cordless screwdriver.



Κωδικός Προϊόντος	Article description	Diameter Area	BX	SDR	Weight kg
613576	FWSG RA 25	d 25	1	11	0,400
613580	FWSG RA 32	d 32	1	11	0,400
613581	FWSG RA 40	d 40	1	11	0,500
613582	FWSG RA 50	d 50	1	11	0,600
613583	FWSG RA 63	d 63	1	11	0,700
613579	Hand crank	универсально	1	-	0,130
613586	Transport box	d 32 - d 63	-	-	0,125

## FWSG RA

### Ξύστρα για σωλήνες και εξόδους d 25 – d 63

#### Application

FRIATOOLS scraper tools for the perfect preparation of HDPE pipe surfaces: Consistently uniform removal of oxide layers for the perfect electrofusion.

#### The crucial difference

Having the correct tools to perform installation on site makes all the difference. We see ourselves as specialists in the electrofusion of HDPE piping systems, so our development work has also included equipment and accessories for your needs from the very outset.

We know exactly what matters and what is needed in the field, and we can offer you a range of equipment tailored to the daily challenges encountered on the building site:

FRIATOOLS scraper tools for all pipe diameters and for a wide range of scrape lengths and saddle surfaces. These safeguard a uniform removal of material and reproducible quality for the optimal processing and reliable fusion of HDPE pipes.

Put your trust in tools that produce the perfect results.

#### Good reasons for the FRIATOOLS scraper tools FWSG RA:

Reliable removal of oxide layers on PE 80, PE 100, and PE-X pipes

Reliable scraping of pipe ends and outlets of fittings, e.g. DAA, DAV, DAP

Extra-long scraping length, also for FRIALONG long couplers

Automatic compensation of pipe out-of-roundness and tolerances

Operation with cordless screwdriver or manual

Quick clamping and easy handling with little effort

Light-weight and compact design for working even in most confined space conditions

Scraper blade designed as turning blade with 2 cutting edges (twice the service life)