

C100

PP Body Conductivity Sensor with SS Electrodes with Temperature Sensor (Pt100) included



Κωδικός προϊόντος	tooltiplimage	Description	Flow Rate Range	Cell Constant	Connection	Installation	Weight (gr.)
C100.01TC	-	Pt100 included	0.1 [CS:Simbolo:μ]S/cm to 2000 [CS:Simbolo:μ]S/cm (10M[CS:Simbolo:Ω] to 500M[CS:Simbolo:Ω] *cm)	0,1	4 poles connector	¾" male BSP (parallel threaded)	350
C100.02TC	-	Pt100 included	0.2 [CS:Simbolo:μ]S/cm to 4000 [CS:Simbolo:μ]S/cm	0,2	4 poles connector	¾" male BSP (parallel threaded)	350
C100.1TC	-	Pt100 included	1 [CS:Simbolo:μ]S/cm to 20000 [CS:Simbolo:μ]S/cm	1	4 poles connector	¾" male BSP (parallel threaded)	350

## C100

- APPLICATIONS β' Agriculture and fertilizing system β' Water treatment β' Foods industry β' Aquaculture β' Ultrapure water application: production and use MAIN FEATURES β' Stainless steel measuring surfaces β' Considerable ratio performance/price β' Temperature sensor included β' Wide range of cell constant β' Rugged sensor body in PP (C100) β' Sensor in SS completely (C300) β' C300.001TCCK with certified cell constant