

VKDFV/CE 24 V AC/DC - ELECTRICALLY ACTUATED DUAL BLOCK® 2-WAY BALL VALVE

DUAL BLOCK® ball valve with female ends, gas cylinder thread with electric actuator 24 V AC/DC



EPDM

Reference	tooltiplmage	R	DN	PN	E	H	H1	L	Z	B	B ₁	g
VKDFVEL038E	-	3/8"	10	16	54	103	65	12**	80	205	29	1785
VKDFVEL012E	-	1/2"	15	16	54	110	65	15	80	205	29	1775
VKDFVEL034E	-	3/4"	20	16	65	116	70	16	83	216	34.5	1903
VKDFVEL100E	-	1"	25	16	73	134	78	19	96	221	39	2011
VKDFVEL114E	-	1" 1/4	32	16	86	153	88	21	110	238	46	2369
VKDFVEL112E	-	1" 1/2	40	16	98	156	93	21	113	244	52	2601
VKDFVEL200E	-	2"	50	*10	122	186	111	26	135	261	62	3218

FKM

Reference	tooltiplmage	R	DN	PN	E	H	H1	L	Z	B	B ₁	g
VKDFVEL038F	-	3/8"	10	16	54	103	65	12**	80	205	29	1785
VKDFVEL012F	-	1/2"	15	16	54	110	65	15	80	205	29	1775
VKDFVEL034F	-	3/4"	20	16	65	116	70	16	83	216	34.5	1903
VKDFVEL100F	-	1"	25	16	73	134	78	19	96	221	39	2011
VKDFVEL114F	-	1" 1/4	32	16	86	153	88	21	110	238	46	2369
VKDFVEL112F	-	1" 1/2	40	16	98	156	93	21	113	244	52	2601
VKDFVEL200F	-	2"	50	*10	122	186	111	26	135	261	62	3218

VKDFV/CE 24 V AC/DC – ELECTRICALLY ACTUATED DUAL BLOCK® 2-WAY BALL VALVE

In addition to the manually actuated version, VKD is also available in VKD/CE electrically actuated and VKD/CP pneumatically actuated configurations. Actuators are firmly connected to the valve by the special FIP Power Quick modules fully made of PP-GR technopolymer. VKD/CE and VKD/CP are constructed with actuators meeting current regulations and selected by FIP according to their quality and reliability requirements. The efficiency of these valves, tested according to the company's quality standards, is guaranteed by the expertise and know-how that FIP dedicates to manufacturing its products.

- Electric actuator constructed according to FIP specifications; with plastic shell and standard emergency override. Available with voltages from 12 to 240V.
- Rack & pinion type pneumatic actuator constructed according to FIP specifications: fully protected against weather corrosion available in double-acting (DA) or simple-acting normally closed (NC) or normally open (NO) versions.
- DUAL BLOCK® patented lock system that ensures union nut tightening hold even in severe conditions such as vibrations or heat dilation.
- Double stem with double O-Rings for ball centring and operating torque reduction. The upper stem is also equipped with a co-moulded steel insert that guarantees high durability and perfect torque transmission between the actuator and ball.
- Sistema di giunzione per incollaggio (solo PVC-U e PVC-C), per saldatura (solo PP-H e PVDF), per filettatura e per flangiatura
- Sistema di supporto della sfera brevettato **SEAT STOP®**, che consente di effettuare una micro-registrazione delle tenute e di minimizzare l'effetto delle spinte assiali
- Facile smontaggio radiale dall'impianto e conseguente rapida sostituzione degli O-Ring e delle guarnizioni della sfera senza l'impiego di alcun attrezzo
- **Corpo valvola a smontaggio radiale** (True union) realizzato per stampaggio ad iniezione in PVC-U, PVC-C, PP-H o PVDF dotato di foratura integrata per l'attuazione.
- Requisiti di prova in accordo ISO 9393 Possibilità di smontaggio delle tubazioni a valle con la valvola in posizione di chiusura
- **Sfera a passaggio totale** di tipo flottante ad alta finitura superficiale
- **Supporto integrato** nel corpo per il fissaggio della valvola La regolazione del supporto della sfera può essere effettuata tramite il **kit di regolazione Easytorque**.