


# CMUIC/CP NO - PNEUMATICALLY ACTUATED COMPACT DIAPHRAGM VALVE DN 12:15

Pneumatically actuated diaphragm valve with unionised metric plain socket ends for solvent welding, Normally Open.





## **EPDM**

Reference		tooltiplmage	d	DN	PN	Е	R <sub>1</sub>	Ra	LA	Z	Н	h	J	g
CMUICNO02	OE	-	20	15	6	41	1"	G 1/4"	90	97.5	129.5	8	M5	340

### **FKM**

Reference	tooltiplmage	d	DN	PN	Е	R <sub>1</sub>	Ra	LA	Z	н	h	J	g
CMUICNO020F	-	20	15	6	41	1"	G 1/4"	90	97.5	129.5	8	M5	340

# **PTFE**

Reference	tooltiplmage	d	DN	PN	Е	R <sub>1</sub>	Ra	LA	Z	Н	h	J	g
CMUICNO020P	-	20	15	6	41	1"	G 1/4"	90	97.5	129.5	8	M5	340





# CMUIC/CP NO - PNEUMATICALLY ACTUATED COMPACT DIAPHRAGM VALVE DN 12:15

The new compact and light piston actuator in PP-GR makes the CM/CP the ideal choice for applications requiring very frequent valve operation and a long valve lifetime.

- Compact and lightweight piston actuator in PP-GR, free of exposed metallic parts, particularly suited for use in severe environmental and chemically aggressive conditions.
- High strength IXEF piston guarantees high reliability over time without maintenance.
- · High visibility graduated optical position indicator protected by a transparent cap with a seal O-Ring.
- · The valve is impervious to fluids containing impurities
- · It has an high flow rate
- · It can be installed in any position
- · It has an extremely compact structure
- It is actuated by a dry running piston and does not require maintenance
- It has no protruding screws and is fully free of impurity deposits
- · Allows for an easy diaphragm seal replacement
- The Standard version valve comes with a position indicator.

