

M9.10.PX – M9.10.WX

Dual Analog Monitor and Transmitter



Reference	tooltiplImage	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.10.P1	-	Panel	12 – 24 VCC	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	550
M9.10.W1	-	Wall	12 – 24 VCC	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	650
M9.10.W2	-	Wall	110 – 230 VCA	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	750

M9.10.PX – M9.10.WX

- APPLICATIONS • Industrial waste water treatment • Civil waste water treatment • Water treatment processes • Processing and Manufacturing industry • Chemical processing • Industrial environment with electromagnetic interferences MAIN FEATURES • Wide graphic display • Multicolor backlight • Help on board • Simultaneous visualization of two parameters • Free setting of engineering unit • Intuitive calibration procedure • In line adjustment • Able to handle active and passive analog signal • USB port for software upgrading