


# CMIF/CP NC - Pneumatically actuated compact diaphragm valve DN 12:15

Pneumatically actuated diaphragm valve with metric plain socket ends for socket welding, Normally Closed.





### EPDM

Reference	tooltipImage	system	Category	family	series	d	DN	PN	Ra	L	н	h	J	g
CMIFNC016E	-	Automation system	Pneumatically actuated valves	Diaphragm valves	CM/CP DN 12÷15	16	12	6	G 1/4"	14	75	8	M5	360
CMIFNC020E	-	Automation system	Pneumatically actuated valves	Diaphragm valves	CM/CP DN 12÷15	20	15	6	G 1/4"	16	75	8	M5	360

#### FKM

Reference	tooltipImage	system	Category	family	series	d	DN	PN	Ra	L	н	h	J	g
CMIFNC016F	-	Automation system	Pneumatically actuated valves	Diaphragm valves	CM/CP DN 12÷15	16	12	6	G 1/4"	14	75	8	M5	360
CMIFNC020F	-	Automation system	Pneumatically actuated valves	Diaphragm valves	CM/CP DN 12÷15	20	15	6	G 1/4"	16	75	8	M5	360

#### PTFE

Reference	tooltipImage	system	Category	family	series	d	DN	PN	Ra	L	Н	h	J	g
CMIFNC016P	-	Automation system	Pneumatically actuated valves	Diaphragm valves	CM/CP DN 12÷15	16	12	6	G 1/4"	14	75	8	M5	360
CMIFNC020P	-	Automation system	Pneumatically actuated valves	Diaphragm valves	CM/CP DN 12÷15	20	15	6	G 1/4"	16	75	8	M5	360





# CMIF/CP NC - Pneumatically actuated compact diaphragm valve DN 12:15

The new compact and light piston actuator in PP-GR makes the CM/CP the ideal choice for applications requiring very frequent valve operation and a long valve lifetime.

- Compact and lightweight piston actuator in PP-GR, free of exposed metallic parts, particularly suited for use in severe environmental and chemically aggressive conditions.
- High strength IXEF piston guarantees high reliability over time without maintenance.
- High visibility graduated optical position indicator protected by a transparent cap with a seal O-Ring.
- The valve is impervious to fluids containing impurities
- It has an high flow rate
- It can be installed in any position
- · It has an extremely compact structure
- It is actuated by a dry running piston and does not require maintenance
- It has no protruding screws and is fully free of impurity deposits
- Allows for an easy diaphragm seal replacement
- The Standard version valve comes with a position indicator.

