

ORP2XX

Bulb ORP Electrodes with epoxy body



Reference	tooltipImage	system	Category	family	series	Features	Operative Range	Cable**	Connection	Installation
ORP200C	-	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Bulb and Flat pH/ ORP Electrodes with Epoxy, C-PVC, Ryton or Glass body	Singol junction	± 2000 mV	Not required	5m (16,5 ft.) Cable	EG50P \$ EG75P \$ MK150200 \$ MIFV20X05 \$ MIMC20X0!
ORP222CD	-	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Bulb and Flat pH/ ORP Electrodes with Epoxy, C-PVC, Ryton or Glass body	Double junction	± 2000 mV	CN 653	Twist-lock (BNC)	EG50P \$ EG75P \$ MIFV20X05 \$ MIMC20X0!
ORP223CD	-	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Bulb and Flat pH/ ORP Electrodes with Epoxy, C-PVC, Ryton or	Double junction for FLS fittings	± 2000 mV	CN 653	Twist-lock (BNC)	F3.SP2.4

ORP2XX

Reference	tooltiplimage	system	Category	family	series	Features	Operative Range	Cable**	Connection	Installation
					Glass body					

ORP2XX

APPLICATIONS:

- Water treatment
- Neutralization systems
- Water quality monitoring
- Swimming Pools and spas
- Aquaculture
- Agriculture and fertilizing systems
- Process control

MAIN FEATURES:

- Epoxy body
- Single or double junction technology
- Large gel reference volume
- Easy and quick installation system
- Outline cable or BNC connection
- Version with temperature sensor combined
- Special versions on request
- Low cost fittings